



## Metrotile Shingle



**Metrotile**<sup>®</sup>  
worldwide roofing systems

### The unique alternative to traditional shingle and slate

**Metrotile Shingle** coated steel tiles imitate the look of traditional flat asphalt shingles, but in lightweight, low-maintenance, long-life steel. They are available in different subtle duotone shades. These tiles are designed for use on roofs as well as vertical walls.

It is now possible to achieve a distinctive look without all the problems inherent in traditional asphalt shingles such as delaminating, lifting and general UV damage.

PRODUCT  
QUALITY  
**100%**  
GUARANTEED

Weatherproof  
guarantee  
of a  
*lifetime*



# Metrotile Shingle

Lightweight high grade steel with Aluzinc® coating for incredible strength and resistance. Suitable for all roof shapes.



## Specifications

Minimum pitch	15°
Maximum pitch	90°
Size of tile - overall	1335 x 300 mm
Size of tile - cover	1235 x 252 mm
Gauge of steel	0.450 mm
Linear cover width	1235 mm
Coverage	0.29 m <sup>2</sup> (3.2 tiles per m <sup>2</sup> )
Weight per m <sup>2</sup>	5.9 kg
Weight per tile	1.75 kg
Colours	The available Shingle standard colours are Red-Brown, Black-Brown and Brown-Black, but is also available in Charcoal, Terracotta, Red, Black, Greenstone, Coffee. Also special colours are available to order (ask your dealer for more information).

## Properties



### Lightweight

Light and easy to handle and install.



### Durable

Colour stability and protects against UV light.



### Stable

Resistance to extreme wind or earthquakes.



### Strong

Exceptional strength and resistant to damage.



### Fire proof

To be conform with the European standards

## Installation of the tiles

The tiling battens for installing the shingle tiles have to be positioned with a 250 mm spacing measured from the front batten of each batten up to the ridge.

Start at the bottom right hand side and work from right to left. Use 4 nails or screws fix each shingle tile to the roof batten. If possible, use the cut-off from the previous to start the next course. Hook nose of upper tile into lip of tile below ensuring a tight fit. Continue with each successive course up.

At the upper course, cut the tiles to suit the ridge and attach a batten on top of the Shingle tile. Finally fix the ridge to the batten.

## More information about the installation?

Please contact your dealer.

## Accessories of the Shingle

Metrotile offers the accessories that fully integrate with the Metrotile Shingle profile.

### Shingle barge board cover and gutter



For closing the edges at the side of a Metrotile Shingle roof.

Overall length:	1355 mm
Cover length:	1345 mm
Cover width:	118 mm
Depth:	90 mm

### Shingle angle ridge



For closing the top rows of shingle tiles.

Overall length:	1355 mm
Cover length:	1345 mm
Cover width:	160 mm

### Shingle starter profile



A starter profile to fix the first row of shingle tiles.

Overall length:	1355 mm
Cover width:	160 mm

For a complete and detailed list of accessories and more information regarding the installation of a Metrotile roof, contact your dealer.